



Miller
INDUSTRIES



4 Car Carriers

THE SOLUTION

for your Multi-Vehicle Transportation Needs

At Miller, we design carriers to help maximize your profit without compromising strength or safety. Our 4-Car Carrier is no exception. By helping to maximize your equipment's payload per mile you can keep the escalating costs of business minimal. The proven 20,000 lb. heavy-duty aluminum carrier decks (available in 28' - 30' bed lengths) combine an independent wheel lift and an over-the-cab deck for the perfect package in multi-vehicle hauling. Chevron's blend of our trusted heavy-duty carrier bed and expertly engineered multi-vehicle design will be a profitable addition to your fleet.

4 Car Carrier

4 Car Carrier

Standard Features

102 in. Wide Aluminum Body
High tensile double box 4 inch extruded floor system
Heavy duty extruded sill w/ integral full length wear strips (top & bottom)
Extruded double-box sides
Full Length Subframe
12 Chain Locks
Fully Hydraulic Wheel Lift
Drop-In L-arms
Mechanical Anti-tilt
18 GPM Direct Mount Pump
Inboard Tilt Cylinders
4 Light Tail Light Housing
Illuminated Dual Controls
8 Side Body Marker Lights (4 per side)
Body Lock
Mudflaps
Federal Standard 108 Lighting
Tow Light Plug
LED Lights
Water Resistant Junction Box for Wire Harness Connection
Lubrication Fittings on All Pivot Points
(2) 8,000 lb. Worm Gear Deck Winches with Tensioners
8,000 lb. Planetary Winch for Cab Carrier
Air Free Spool on All Winches (Drivers Side)
Pilot Operated Holding Valves on Tilt & Lift Functions
Backup Alarm
4 Safety Chains

Accessories

Work Lights
Switch Panel
Magnetic Tow Lights
J-Hook Chains
Front Hookup Chain
Trailer Ball Plate
Pintle Hook Attachment

Chassis Recommendations

Recommended GVWR – 33,000 lbs
Accessible PTO opening
Maximum Frame Height – 42 inches
Minimum Frame Height – 36 inches

Optional Features

Additional Chain Locks
24 GPM Direct Mount Pump
PTO
Retractable Ladder
Various Toolbox Options
Factory Installation
Pivoting L-arms
AutoGrip™ II Wheel Lift
Galvanized Subframe
Wireless Remote Control
Passenger Side Air Free Spool

Note: Some option selections may not be compatible in all configurations.

Specifications

Body Width	97 I.D. x 102 O.D.
Body Extension	120 inches
Control Valve	Sectional, 20 GPM, 2400 PSI
Oil Reservoir	12 Gallons
Oil Filter	250 PSI, 25 Microns
Pump	18 GPM
Body Rating*	20,000 lbs. evenly distributed
Wheel Lift Rating*	4,000 lbs. extended
Cab Carrier Rating*	5,000 lbs. evenly distributed

*Load ratings are based on structural factors – not chassis capability or capacity

Carrier Length	Usable Cab-To-Axle (w/ cab carrier)	Minimum Frame RBM (each rail)
28	202	1,800,000 in * lbs
29	210	2,100,000 in * lbs
30	218	2,100,000 in * lbs

Miller 4-car carriers should be mounted on chassis with low profile cabs and a minimum FAWR 12,000 lbs. for the cab carrier.