



# Power, Performance, and Value

Vulcan's 804 provides the power and performance for light duty towing at a very affordable price. The integrated boom and wheel lift is designed to save weight, thus allowing you the potential for increased legal payload without overloading the chassis. Reliability in your towing equipment is also essential in today's competitive marketplace and the Vulcan 804 is built to meet that challenge with the same quality found in all Vulcan products. The 804 is one of the easiest and safest units to tow with today using Vulcan's patented strapless wheel lift system. The retainers pivot horizontally as well as vertically for easy hookups in a wide variety of situations. The best part is there are no tie down straps. Contact your Vulcan distributor to find out how the Vulcan 804 can fill your towing needs without overloading your budget.

Innovative. Durable.
Brutally Tough.

# Innovative. Durable. Brutally Tough.

#### **SPECIFICATIONS**

SI LCII ICATIONS	
BOOM	
Recovery Boom (at boom end swivel)	8,000 lbs.
Winch	
Cable	3/8" x 100'
UNDERLIFT	
Lift Capacity Extended	4,000 lbs.
Tilt Angles	
Tow Rating	
Maximum Reach	61"
CHASSIS RECOMMENDATION	
Minimum C.A. (Cab to Axle)	60"
Maximum C.A. (With Tunnel Tool Box)	
Suggested GVWR	





### STANDARD FEATURES

- Vulcan's Patented 4,000 lb. Wheel Retainers
- Adjustable Width Modular Body, 88" or 94"
- 60" Cab-to-Axle Steel Body
- Driver & Passenger Side Controls
- Tailboard Safety Chain Pockets
- Safety Chain Pocket Guards
- Wheel Lift Safety Chains 5/16, Grade 70
- Wheel Retainer Storage Pockets
- Driver & Passenger Side Tool Compartments
- 8,000 lb. Winch with 100' of 3/8" Cable
- Winch Free Spool and Cable Tensioner
- Mud Flaps
- Federal Standard 108 Lighting

## **OPTIONAL FEATURES**

- 60" C.A. Aluminum Modular Body
- 60" C.A. Composite Modular Body (94" Wide Only)
- Light Pylon
- Aluminum Tubular Light Pylon
- 24" Tunnel Tool Box
- Sling Attachment
- Trailer Hitch
- Dress Up Packages
- Additional Lighting
- PTO
- Wheel Simulators



All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.





**DISTRIBUTED BY:** 

8503 Hilltop Drive • Ooltewah, TN 37363 800-489-2401 • 423-238-7227 FAX 800-960-6667 • www.MILLERIND.com